NSN 4720-00-310-1924

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-310-1924

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.313 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8

NSN 4720-00-310-1924

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
70.250 inches working	
Media For Which Designed:	
Alcohol single response and fuel/oil, hydrocarbon single response and solvent single response and water single response	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	