NSN 4720-00-311-7496

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-311-7496

| view Offilite at https://aerobasegroup.com/hsr//4/20-00-311-74-30 |
|--|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.313 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Hose Or Tubing Specification/std Data: |
| Mil mil-h-27267, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel comp 304 all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting passivate 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 24 2nd end |
| Second End Relationship With First End: |
| Not identical |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |

0.438 inches 1st end

Thread Size:

1500.0 pounds per square inch

NSN 4720-00-311-7496

Nonmetallic Hose Assembly - Page 2 of 2



| Seat Angle: |
|---|
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 96.500 inches working |
| Second End Swivel Action Capability: |
| Not included |
| Special Features: |
| Inner conveying tube material-plastic, polytetrafluoroethylene |
| Media For Which Designed: |
| Alcohol and fuel/oil, hydrocarbon and solvent and water single response |
| Thread Series Designator: |
| Unjf 1st end |
| Specification Data: |
| Mil mil-h-27267, size 4 professional/industrial association specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |