NSN 4720-00-314-0362

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Unf 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-314-0362

Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
27 2nd end
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber and 1st layer braided steel wire
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.125 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

NSN 4720-00-314-0362

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0