Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-314-0483

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.187 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.515 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated braided cotton cord and 1st layer braided wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4720-00-314-0483

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

