Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-314-0748

view Online at https://aeiobasegioup.com/hsi//4/20-00-514-0/40	
Cross Sectional Shape:	
Round	
Thread Class:	
2a 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Outside Diameter:	
0.438 inches	
Connection Style:	
Swivel nut, inverted flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external tube 1st end	
Thready Qty Per Inch (tpi):	
24 1st end	
Burst Test Pressure:	
1700.0 pounds per square inch	
Layer Composition And Location:	
Outer layer rubber impregnated braided rayon cord and 1st layer braided cotton cord	
Maximum Operating Pressure:	
425.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Hydrostatic Test Pressure:	
850.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant and oil resistant and vibration resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
7.500 inches	
Thread Series Designator:	
Uns 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

--

## NSN 4720-00-314-0748

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

