NSN 4720-00-314-0748

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-314-0748

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Outside Diameter:
0.438 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
1700.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated braided rayon cord and 1st layer braided cotton cord
Maximum Operating Pressure:
425.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
850.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and vibration resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.500 inches
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-314-0748

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0