Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-317-4115

Round

**Thread Class:** 

2b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.380 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.840 inches

Minimum Inside Bending Radius:

#### 5.000 inches

**Exterior Color:** 

Black

## **End Application:**

Grumman a10 aircraft

#### **Connection Style:**

Swivel nut flare 1st end

## End Connection Design:

Straight 1st end

#### Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Reusable end fittings

## **Burst Test Pressure:**

16000.0 pounds per square inch

## Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic

# Maximum Operating Pressure:

4000.0 pounds per square inch

## Thread Size:

0.750 inches 1st end

## Seat Angle:

37.0 degrees 1st end

## Hydrostatic Test Pressure:

8000.0 pounds per square inch

# **Outer Covering Environmental Protection:**

Oil resistant and ozone resistant and weatherproof

# Inside Surface Condition:

Smooth

# NSN 4720-00-317-4115

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length:

36.000 inches

## Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

## **Thread Series Designator:**

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A542a0