Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-317-4155

| Cross | Sectional | Shape: |
|-------|-----------|--------|
|-------|-----------|--------|

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Outside Diameter:

0.500 inches

Connection Style:

Flared 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

NSN 4720-00-317-4155

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

