NSN 4720-00-318-0478

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0478 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.672 inches **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.625 inches 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Outer Covering Environmental Protection:** Fire retardant and hydraulic solution resistant and mildew resistant and oil resistant **Inside Surface Condition:** Smooth Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4720-00-318-0478

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0