NSN 4720-00-318-0483

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0483

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.578 inches |
| Connection Style: |
| Swivel nut with compression sleeve 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 27 2nd end |
| Burst Test Pressure: |
| 10000.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 1st end |
| Seat Angle: |
| 30.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 5000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant and water resistant and cold resistant and alcohol |
| resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 13.625 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |

Unf 1st end

NSN 4720-00-318-0483

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0