## NSN 4720-00-318-0559

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0559

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 1.250 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                                    |
| Outside Diameter:  |
| 2.000 inches   |
| Minimum Inside Bending Radius:   |
| 16.000 inches  |
| Connection Style:  |
| Plain 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external pipe 1st end   |
| Burst Test Pressure:   |
| 6500.0 pounds per square inch  |
| Layer Composition And Location:  |
| 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure:  |
| 1625.0 pounds per square inch  |
| Thread Size:   |
| 1.250 inches 1st end   |
| Hydrostatic Test Pressure:   |
| 3250.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Mildew resistant and oil resistant and oil resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 85.500 inches  |
| Thread Series Designator:  |
| Npt 1st end  |
| Specification Data:  |
| 81349-mil-h-13531 government specification   |
| Specification Or Standard:   |
| 2 type and a class   |
| Shelf Life:  |

N/a

## NSN 4720-00-318-0559

Nonmetallic Hose Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0