Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0575

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
2.000 inches	
Minimum Inside Bending Radius:	
16.000 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
6500.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
1625.0 pounds per square inch	
Thread Size:	
1.250 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
3250.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
77.500 inches	
Thread Series Designator:	
Npt 1st end	
Specification Data:	
81349-mil-h-13531 government specification	
Specification Or Standard:	
2 type and a class	

## NSN 4720-00-318-0575

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

