Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0580

C	Cross Sectional Shape:
-	Round
Т	hread Direction:
F	Right-hand 1st end
lı	nside Diameter:
0	.375 inches
Т	empurature Rating:
-(65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
C	Dutside Diameter:
0	1.843 inches
N	/inimum Inside Bending Radius:
5	0.000 inches
C	Connection Style:
Ir	nverted flare 1st end
E	Ind Connection Design:
S	Straight 1st end
C	Connection Type:
Т	hreaded external pipe 1st end
B	Burst Test Pressure:
1	4000.0 pounds per square inch
L	ayer Composition And Location:
2	nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber
N	laximum Operating Pressure:
3	500.0 pounds per square inch
Т	hread Size:
0	.375 inches 1st end
S	Seat Angle:
3	0.0 degrees 1st end
F	lydrostatic Test Pressure:
7	000.0 pounds per square inch
C	Duter Covering Environmental Protection:
N	fildew resistant and oil resistant and oil resistant
h	nside Surface Condition:
S	Smooth
N	leasuring Method And Length:
1	27.000 inches
Т	hread Series Designator:
Ν	lptf 1st end
S	pecification Data:
8	1349-mil-h-13531 government specification
S	Specification Or Standard:
2	type and a class

NSN 4720-00-318-0580

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

