Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0581

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.750 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
1.250 inches	
Minimum Inside Bending Radius:	
9.500 inches	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubbe	r
Maximum Operating Pressure:	
2250.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Oil resistant and ozone resistant and mildew resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
66.000 inches	
Thread Series Designator:	
Nptf 1st end	
Specification Data:	
81349-mil-h-13531 government specification	
Specification Or Standard:	
2 type and a class	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.