## NSN 4720-00-318-0584

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0584

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.843 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer helix aluminum alloy coil and outer layer molded rubber
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
116.000 inches
Thread Series Designator:
Nptf 1st end
Specification Data:
81349-mil-h-13531 government specification
Specification Or Standard:

2 type and a class

## NSN 4720-00-318-0584

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0