NSN 4720-00-318-0585

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0585

Cross Sectional Shape					
Cross Sectional Shape:					
Round Thread Birections					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
0.687 inches					
Minimum Inside Bending Radius:					
4.000 inches					
Connection Style:					
Plain 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded external pipe 1st end					
Burst Test Pressure:					
20000.0 pounds per square inch					
Layer Composition And Location:					
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber					
Maximum Operating Pressure:					
5000.0 pounds per square inch					
Thread Size:					
0.250 inches 1st end					
Hydrostatic Test Pressure:					
10000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Mildew resistant and oil resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
17.000 inches					
Thread Series Designator:					
Nptf 1st end					
Specification Data:					
81349-mil-h-13531 government specification					
Specification Or Standard:					
2 type and a class					
Shelf Life:					

N/a

NSN 4720-00-318-0585

Nonmetallic Hose Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.