## NSN 4720-00-318-0589

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0589

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.250 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                       |
| Outside Diameter:   |
| 0.687 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| Connection Style:   |
| Plain 1st end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Burst Test Pressure:  |
| 18000.0 pounds per square inch  |
| Layer Composition And Location:   |
| 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber |
| Maximum Operating Pressure:   |
| 4500.0 pounds per square inch   |
| Thread Size:  |
| 0.250 inches 1st end  |
| Hydrostatic Test Pressure:  |
| 9000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Mildew resistant and oil resistant and oil resistant and hydraulic solution resistant       |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 35.000 inches   |
| Thread Series Designator:   |
| Nptf 1st end  |
| Specification Data:   |
| 81349-mil-h-13531 government specification  |
| Specification Or Standard:  |
| 2 type and a class  |
| Shelf Life:   |

## NSN 4720-00-318-0589

Nonmetallic Hose Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0