NSN 4720-00-318-0593

Cross Sectional Shape:

Between 0.242 inches and 0.273 inches

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Thread Series Designator:

Npt 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0593

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.656 inches and 0.718 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber and 1st layer braided steel wire
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
231.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

NSN 4720-00-318-0593

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0