Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0940

**Cross Sectional Shape:** 

Round

**Thread Direction:** 

Right-hand 1st end

Inside Diameter:

2.000 inches

Outside Diameter:

2.750 inches

## Hose Or Tubing Specification/std Data:

Fed zz-h-561 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## First End Fitting Specification/std Data:

Ww-c-624, type b, style 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Second End Fitting Specification/std Data:

Ww-c-624, type b, style 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut, gasket seal 1st end

**End Connection Design:** Straight 2nd end **End Fitting Component And Material:** Complete fitting copper alloy all ends **Connection Type:** Threaded internal hose 1st end Second End Relationship With First End: Not identical **Burst Test Pressure:** 300.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer rubber impregnated fabric Thread Size: 2.000 inches 1st end **Hydrostatic Test Pressure:** 100.0 pounds per square inch **Inside Surface Condition:** Smooth Measuring Method And Length: 120.000 inches

Second End Swivel Action Canability:



Media For Which Designed: Water, fresh single response **Thread Series Designator:** Npsh 2nd end Specification Data: 81348-zz-h-561 government specification **Specification Or Standard:** 1 type and b style and b grade and 2 class Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0