Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-0969

Cross Sectional Sha	be:
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating	
-65.0 degrees fahrenh	eit and 125.0 degrees fahrenheit single response
Outside Diameter:	
0.906 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Des	gn:
Straight 1st end	
Connection Type:	
Threaded external pip	e 1st end
Burst Test Pressure:	
7000.0 pounds per sq	uare inch
Layer Composition	nd Location:
Outer layer molded ru	bber, buna-n and 1st layer braided steel wire
Maximum Operating	Pressure:
1750.0 pounds per sq	uare inch
Thread Size:	
0.500 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pre	ssure:
3500.0 pounds per sq	Jare inch
Outer Covering Envi	conmental Protection:
Oil resistant	
Inside Surface Cond	tion:
Smooth	
Measuring Method A	nd Length:
45.000 inches	
Thread Series Desig	nator:
Nptf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-00-318-0969

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

