

View Online at <https://aerobasegroup.com/nsn/4720-00-318-0974>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-60.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

3.750 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

900.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided textile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

225.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

450.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and fuel resistant and hydraulic solution resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.000 inches

**Special Features:**

Furnished w/one adpter st ipe to tube ext thds .250-18 nptf, 0.750-20 unef

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unef 1st end

**Specification Data:**

81349-mil-h-3992 government specification

**Specification Or Standard:**

1 type and 1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.