

View Online at <https://aerobasegroup.com/nsn/4720-00-318-1019>

Cross Sectional Shape:

Round

Inside Diameter:

3.000 inches

Temperature Rating:

-32.0 degrees celsius and 52.0 degrees celsius single response

Outside Diameter:

3.750 inches

Hose Or Tubing Specification/std Data:

Mil-h-370, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

3.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided cotton cord

Hydrostatic Test Pressure:

150.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

172.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Specification Data:

Mil-h-370, type 2 professional/industrial association specification and 81349-mil-h-370 government specification

Specification Or Standard:

2 type and 8 size and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-370 spec.