

View Online at <https://aerobasegroup.com/nsn/4720-00-318-1019>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

3.000 inches

**Temperature Rating:**

-32.0 degrees celsius and 52.0 degrees celsius single response

**Outside Diameter:**

3.750 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-370, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Quick Disconnect Size:**

3.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Internal quick disconnect 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

500.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

2nd layer braided cotton cord

**Hydrostatic Test Pressure:**

150.0 pounds per square inch

**Outer Covering Environmental Protection:**

Ozone resistant and fuel resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

172.000 inches excluding end fittings

**Second End Swivel Action Capability:**

Not included

**Specification Data:**

Mil-h-370, type 2 professional/industrial association specification and 81349-mil-h-370 government specification

**Specification Or Standard:**

2 type and 8 size and 1 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-370 spec.