NSN 4720-00-318-1112

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-1112

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.844 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
79.750 inches and 80.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4720-00-318-1112

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0