Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-318-1112

| Cross Sectional Shape: | |
|--|--|
| Round | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.375 inches | |
| Tempurature Rating: | |
| -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.844 inches | |
| Minimum Inside Bending Radius: | |
| 5.000 inches | |
| Connection Style: | |
| Plain 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded external pipe 1st end | |
| Thready Qty Per Inch (tpi): | |
| 18 1st end | |
| Burst Test Pressure: | |
| 1600.0 pounds per square inch | |
| Layer Composition And Location: | |
| 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene | |
| Maximum Operating Pressure: | |
| 4000.0 pounds per square inch | |
| Thread Size: | |
| 0.375 inches 1st end | |
| Hydrostatic Test Pressure: | |
| 8000.0 pounds per square inch | |
| Outer Covering Environmental Protection: | |
| Mildew resistant and oil resistant and oil resistant | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 79.750 inches and 80.250 inches | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single response | |
| Thread Series Designator: | |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0