NSN 4720-00-320-0740

Nonmetallic Hose Assembly - Page 1 of 2



Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.313 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response			
Outside Diameter:			
0.672 inches			
Minimum Inside Bending Radius:			
5.000 inches			
Exterior Color:			
Black			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord			
Maximum Operating Pressure:			
2250.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
4500.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
18.000 inches			
Special Features:			
W/one an815-6 adapter and one an832-6 adapter			

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-00-320-0740

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0