NSN 4720-00-320-9263

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-320-9263 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -15.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.578 inches **Minimum Inside Bending Radius:** 3.380 inches **Exterior Color:** Red **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided cotton cord and 1st layer braided wire **Maximum Operating Pressure:** 350.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 600.0 pounds per square inch **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth

Measuring Method And Length: 12.000 inches

Media For Which Designed:

Refrigerant 12 and refrigerant 13 single response

NSN 4720-00-320-9263

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: | hread Se | ries D | esignator: |
|---------------------------|----------|--------|------------|
|---------------------------|----------|--------|------------|

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0