Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-320-9263

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-15.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.578 inches
Minimum Inside Bending Radius:
3.380 inches
Exterior Color:
Red
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided cotton cord and 1st layer braided wire
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Media For Which Designed:
Refrigerant 12 and refrigerant 13 single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0