Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-324-3389

# **Cross Sectional Shape:**

Round

## **Thread Class:**

3b 1st end

# **Thread Direction:**

Right-hand 1st end

## **Inside Diameter:**

0.188 inches

### **Tempurature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

### **Outside Diameter:**

0.312 inches

### Minimum Inside Bending Radius:

2.000 inches

### **Exterior Color:**

Natural

### **Connection Style:**

Swivel nut flare 1st end

## End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Electrostatic discharge capability and reusable end fittings

## **Burst Test Pressure:**

12000.0 pounds per square inch

## Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

## Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.438 inches 1st end

## Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

3000.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Corrosion resistant

Vacuum In Torr:

50.8

### Inside Surface Condition:

Smooth



Measuring Method And Length:

71.000 inches working

**Thread Series Designator:** 

Unjf 1st end

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0