Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-325-6558

| Cros | s Sectional Shape: |
|-------|---|
| Rour | nd |
| Thre | ad Direction: |
| Right | t-hand 1st end |
| Insid | le Diameter: |
| 0.312 | 2 inches |
| Tem | purature Rating: |
| | 0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response |
| Outs | ide Diameter: |
| 0.438 | 3 inches |
| Minii | num Inside Bending Radius: |
| 4.000 |) inches |
| Conr | nection Style: |
| Swiv | el nut flare 1st end |
| End | Connection Design: |
| Elbov | w 1st end |
| Conr | nection Type: |
| Threa | aded internal tube 1st end |
| Burs | t Test Pressure: |
| 9000 | .0 pounds per square inch |
| Laye | r Composition And Location: |
| Oute | r layer braided corrosion resistant steel wire |
| Maxi | mum Operating Pressure: |
| 1000 | .0 pounds per square inch |
| Thre | ad Size: |
| 0.562 | 2 inches 1st end |
| Seat | Angle: |
| 37.0 | degrees 1st end |
| Flow | Angle: |
| 90.0 | degrees 1st end |
| Insid | le Surface Condition: |
| Smo | oth |
| Meas | suring Method And Length: |
| 30.00 | 00 inches working |
| Thre | ad Series Designator: |
| Unf 1 | st end |
| Shel | f Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| Dem | ilitarization: |
| No | |

NSN 4720-00-325-6558

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

