Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-331-6886

C	ross Sectional Shape:
	bund
	nread Class:
) 1st end
-	nread Direction:
	ght-hand 1st end side Diameter:
	625 inches
-	
	empurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
-	781 inches
	inimum Inside Bending Radius:
	500 inches
	onnection Style:
	vivel nut flare 1st end
	nd Connection Design:
	raight 1st end
	onnection Type:
	nreaded internal tube 1st end
	nready Qty Per Inch (tpi):
	2 1st end
_	urst Test Pressure:
	00.0 pounds per square inch
	ayer Composition And Location:
	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
10	00.0 pounds per square inch
Tł	nread Size:
1.	062 inches 1st end
Se	eat Angle:
37	7.0 degrees 1st end
H	vdrostatic Test Pressure:
20	000.0 pounds per square inch
Μ	easuring Method And Length:
14	1.250 inches working
Tł	nread Series Designator:
Uı	n 1st end
SI	nelf Life:
N/	'a
U	nit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

