

View Online at <https://aerobasegroup.com/nsn/4720-00-333-5415>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.777 inches

Minimum Inside Bending Radius:

5.000 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and 1st layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0