## NSN 4720-00-334-4649

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-334-4649

Tempurature Rating:				
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response				
Outside Diameter:				
0.312 inches				
Minimum Inside Bending Radius:				
2.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Electrostatic discharge capability				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Vacuum In Torr:				
50.8				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
34.000 inches working				
Thread Series Designator:				
Unjf 1st end				

## NSN 4720-00-334-4649

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

96906-ms8000 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0