NSN 4720-00-334-6988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-334-6988

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end Inside Diameter:
0.250 inches
Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.578 inches
Minimum Inside Bending Radius:
3.375 inches
Exterior Color:
Black
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and 1st layer braided rayon cord and outer layer rubber impregnated cotton fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.125 inches 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-334-6988

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0