Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-345-1081

Cross S	Sectional Shape:
Round	
Thread	Class:
3b 1st e	nd
Thread	Direction:
Right-ha	and 1st end
Inside D	Diameter:
0.875 in	ches
Tempur	rature Rating:
-65.0 de	grees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside	Diameter:
1.109 in	ches
Minimu	m Inside Bending Radius:
7.375 in	ches
Connec	tion Style:
Swivel n	nut flare 2nd end
End Co	nnection Design:
Straight	1st end
Connec	tion Type:
Threade	ed internal tube 1st end
Burst T	est Pressure:
5000.0 p	pounds per square inch
Layer C	composition And Location:
Outer la	yer braided corrosion resistant steel wire
Maximu	Im Operating Pressure:
1250.0 p	pounds per square inch
Thread	Size:
1.375 in	ches 2nd end
Seat An	igle:
37.0 deç	grees 2nd end
Hydrost	tatic Test Pressure:
2500.0 p	pounds per square inch
Flow Ar	ngle:
90.0 deç	grees 2nd end
Inside S	Surface Condition:
Smooth	
Measur	ing Method And Length:
45.000 i	nches working
Thread	Series Designator:
Unjf 1st	end
Shelf Li	fe:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0