Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-348-0692

C	ross Sectional Shape:
R	ound
Т	hread Class:
3Ł	o 1st end
TI	hread Direction:
Ri	ight-hand 1st end
In	side Diameter:
0.	188 inches
Te	empurature Rating:
-1	00.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	utside Diameter:
0.	312 inches
C	onnection Style:
S	wivel nut flare 1st end
E	nd Connection Design:
St	traight 1st end
C	onnection Type:
Tł	hreaded internal tube 1st end
В	urst Test Pressure:
12	2000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
15	500.0 pounds per square inch
TI	hread Size:
0.	438 inches 1st end
S	eat Angle:
37	7.0 degrees 1st end
H	ydrostatic Test Pressure:
60	000.0 pounds per square inch
Μ	easuring Method And Length:
29	9.000 inches working
TI	hread Series Designator:
-	nf 1st end
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A!	542a0