

View Online at <https://aerobasegroup.com/nsn/4720-00-349-3124>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.312 inches 2nd end

Outside Diameter:

2.219 inches

Minimum Inside Bending Radius:

13.250 inches

Exterior Color:

Black or gray

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 2nd end

Flange Width:

3.000 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.344 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

2nd layer rubber impregnated braided steel wire and 1st layer rubber impregnated braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

350.0 pounds per square inch

Thread Size:

2.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

73.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

54.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0