Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-350-5875

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Thready Qty Per Inch (tpi):	
18 1st end	
Burst Test Pressure:	
15000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
42.0 degrees 1st end	
Hydrostatic Test Pressure:	
7000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.000 inches	
Special Features:	
Thd maximum pitch diameter modified from standardto be 0.7180 in.	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Uns 1st end	

NSN 4720-00-350-5875

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

