## NSN 4720-00-350-8791

Nonmetallic Hose Assembly - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/4720-00-350-8791

View Online at https://aerobasegroup.com/nsn/4720-00-350-8791
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.750 inches and 0.812 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Specification Or Standard:

6 size

## NSN 4720-00-350-8791

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0