## NSN 4720-00-351-7311

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-351-7311

The first of the street of the
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.000 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
608.000 inches
Special Features:

Furnished with three rubber washers

## NSN 4720-00-351-7311

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Water single response
Thread Series Designator:
Nh 2nd end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0