Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-354-5826

| Cross Sectional Sha | ape: |
|------------------------|--|
| Round | |
| Thread Class: | |
| 2b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.500 inches | |
| Tempurature Rating | J: |
| -40.0 degrees fahren | heit and 200.0 degrees fahrenheit single response |
| Connection Style: | |
| Swivel nut flare 1st e | nd |
| End Connection De | sign: |
| Straight 2nd end | |
| Connection Type: | |
| Threaded internal tub | be 1st end |
| Burst Test Pressure | 2: |
| 7000.0 pounds per se | quare inch |
| Layer Composition | And Location: |
| 2nd layer sheet rubb | er and 1st layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating | y Pressure: |
| 1750.0 pounds per se | quare inch |
| Thread Size: | |
| 0.875 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 1st end | I |
| Inside Surface Con | dition: |
| Smooth | |
| Measuring Method | And Length: |
| 15.250 inches | |
| Media For Which De | esigned: |
| Hydraulic fluid single | response |
| Thread Series Desig | gnator: |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A542a0 | |