NSN 4720-00-354-8911

Cross Sectional Shape:

Thread Direction:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-354-8911

Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.969 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded external pipe 1st end
Features Provided:
Features Provided: Electrostatic discharge capability
Electrostatic discharge capability
Electrostatic discharge capability Thready Qty Per Inch (tpi):
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer braided steel wire
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer braided steel wire Maximum Operating Pressure:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer braided steel wire Maximum Operating Pressure: 3500.0 pounds per square inch
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer braided steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 14 1st end Second End Relationship With First End: Identical Burst Test Pressure: 14000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer braided steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.500 inches 1st end

Abrasion resistant and light resistant and weatherproof

NSN 4720-00-354-8911

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
19.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0