

View Online at <https://aerobasegroup.com/nsn/4720-00-356-2048>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper all ends

Connection Type:

Threaded external tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1200.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided cotton cord

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.500 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0