## NSN 4720-00-356-6572



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-356-6572 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting copper alloy all ends **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 20 1st end Second End Relationship With First End: Identical **Burst Test Pressure:** 1000.0 pounds per square inch First End Swivel Action Capability: Not included **Layer Composition And Location:** Outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch

250.0 pounds per squ
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end

## NSN 4720-00-356-6572

Nonmetallic Hose Assembly - Page 2 of 2



## **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 17.750 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A542a0