NSN 4720-00-356-8557

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-356-8557

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Outside Diameter: |
| 0.594 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal pipe 1st end |
| Burst Test Pressure: |
| 700.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer rubber impregnated braided cotton cord and 1st layer rubber impregnated braided cotton cord and outer layer molded rubber |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 300.000 inches excluding end fittings |
| Special Markings: |
| Air |
| Thread Series Designator: |
| Npsm 1st end |
| Specification Data: |
| 81348-zz-h-461 government specification |
| Specification Or Standard: |
| A style |
| Shelf Life: |

NSN 4720-00-356-8557

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A542a0