Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-356-8562

tound hread Direction: tight-hand 1st end side Diameter: .750 inches Dutside Diameter: .750 inches Dutside Diameter: .750 inches Exterior Color: .812 inches Exterior Color: .812 inches Exterior Color: .814 Acc Connection Style: .822 inches .823 Connection Design: .824 Connection Design: .825 Connection Design: .825 Connection Type: .825 Conn	
tight-hand 1st end hside Diameter:	
Inside Diameter: .750 inches Putside Diameter: .812 inches .812 inches exterior Color: lack connection Style: wivel nut, inverted flare 1st end ind Connection Design: atraight 1st end connection Type: hreaded internal pipe 1st end Burst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Puter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end eat Angle: 0.0 degrees 1st end buter Covering Environmental Protection: .00.0 pounds per square inch buter Covering Environmental Protection: .brasion resistant and oil resistant leasuring Method And Length: 00.000 inches	
.750 inches butside Diameter: .812 inches exterior Color: lack connection Style: wivel nut, inverted flare 1st end ind Connection Design: etraight 1st end connection Type: hreaded internal pipe 1st end Burst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: buter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end etat Angle: 0.0 degrees 1st end buter Covering Environmental Protection: buter Covering Environmental Protection: brasion resistant and oil resistant leasuring Method And Length: 00.000 inches	
Autside Diameter: .812 inches .812 inches exterior Color: lack connection Style: evivel nut, inverted flare 1st end ind Connection Design: etraight 1st end connection Type: hreaded internal pipe 1st end burst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: buter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end etat Angle: 0.0.0 degrees 1st end buter Covering Environmental Protection: buter Covering Environmental Protection: burst Test Pressure: 0.0.0 pounds per square inch ager Angle: 0.0.0 pounds per square inch buter Covering Environmental Protection: buter Covering Environmental Protection: buter Covering Environmental Protection: buter Covering Method And Length: 00.000 inches	
.812 inches ixterior Color: lack connection Style: wivel nut, inverted flare 1st end ind Connection Design: itraight 1st end connection Type: hreaded internal pipe 1st end itrast Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end itet Angle: 0.0.0 pounds per square inch itet Angle: 0.0.1 degrees 1st end itet Angle: 0.0.2 pounds per square inch itet Angle: 0.0.3 pounds per square inch itet Angle: 0.0.4 pounds per square inch itet Angle: 0.0.3 pounds per square inch itet Angle: 0.0.4 pou	
Axterior Color: idack connection Style: wivel nut, inverted flare 1st end ind Connection Design: itraight 1st end connection Type: hreaded internal pipe 1st end itrast Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end ideat Angle: 0.0 degrees 1st end bydrostatic Test Pressure: 00.0 pounds per square inch ideat Angle: 0.0 degrees 1st end ideat Angle: 0.0.1 pounds per square inch ideat Angle: 0.0 pounds per square inch ideat Angle: 0.0 pounds per square inch ideat Angle: 0.0.2 pounds per square inch ideat Angle:	
liack connection Style: wivel nut, inverted flare 1st end connection Design: straight 1st end connection Type: hreaded internal pipe 1st end connection Type: hreaded internal pipe 1st end context Test Pressure: 00.0 pounds per square inch ayer Composition And Location: buter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end ceat Angle: 0.0 degrees 1st end buter Covering Environmental Protection: brasion resistant and oil resistant Reasuring Method And Length: 00.000 inches	
Connection Style: wivel nut, inverted flare 1st end sind Connection Design: straight 1st end connection Type: hreaded internal pipe 1st end hurst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric thread Size: .750 inches 1st end eaet Angle: 0.0.0 gounds per square inch updrostatic Test Pressure: 0.0.1 pounds per square inch ideat Angle: 0.2.2 pounds per square inch updrostatic Test Pressure: 0.0.2 pounds per square inch updrostatic Test Pressure: 0.2.2 pounds per square inch updrostatic Test Pressure: 0.2.2 pounds per square inch updrostatic Test Pressure: updrostatic Testert pounomental Protection:	
wivel nut, inverted flare 1st end ind Connection Design: itraight 1st end connection Type: hreaded internal pipe 1st end surst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end eaet Angle: 0.0 degrees 1st end lydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: brasion resistant and oil resistant leasuring Method And Length: 00.000 inches	
And Connection Design: Attraight 1st end Connection Type: Arreaded internal pipe 1st end Aurst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric Arread Size: 750 inches 1st end Arread Angle: 0.0 degrees 1st end Mydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: brasion resistant and oil resistant Areasuring Method And Length: 00.000 inches	
Attraight 1st end Connection Type: A freaded internal pipe 1st end Connection Type: A freaded internal pipe 1st end Connection Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric Thread Size: .750 inches 1st end .750 inches 1st end .750 inches 1st end .750 on degrees 1st end .750 on degrees 1st end .750 pounds per square inch .750 on degrees 1st end .750 inches	
Connection Type: Ihreaded internal pipe 1st end Burst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric Ihread Size: 750 inches 1st end Beat Angle: 0.0 degrees 1st end Bydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: Ibrasion resistant and oil resistant Beasuring Method And Length: 00.000 inches	
hreaded internal pipe 1st end surst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric inread Size: .750 inches 1st end .750 inches 1st end .750 onches 1st end .750 onches 1st end .750 pounds per square inch .750 pounds	
Aurst Test Pressure: 00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end .750 inches 1st end .750 inches 1st end .750 on degrees 1st end .00 degrees 1st end .00 degrees 1st end .00 pounds per square inch .00.0 pounds per square inch .01.0 pounds per square inch .02.0 pounds per square inch .03.0 pounds per square inch .04.0 pounds per square inch .05.0 pounds per square inch	
00.0 pounds per square inch ayer Composition And Location: Duter layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end .750 inches 1st end .750 ouches 1st end .00 degrees 1st end .00 degrees 1st end .00 pounds per square inch .00.0 pounds per square inch .01.0 pounds per square inch .02.0 resistant and oil resistant .03.000 inches	
ayer Composition And Location: Outer layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end ceat Angle: 0.0 degrees 1st end hydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: .brasion resistant and oil resistant Heasuring Method And Length: 00.000 inches	
Outer layer molded rubber, natural and 1st layer rubber impregnated cotton fabric hread Size: .750 inches 1st end .750 inches 1st end .750 degrees 1st end .750 degrees 1st end .750 outer Covering Environmental Protection: .750 inches 1st end .750 inches .750 inches .7	
Thread Size: .750 inches 1st end .750 inches 1st end 	
.750 inches 1st end eat Angle: 0.0 degrees 1st end lydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: brasion resistant and oil resistant leasuring Method And Length: 00.000 inches	
Geat Angle: 0.0 degrees 1st end Iydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: ubrasion resistant and oil resistant Ideasuring Method And Length: 00.000 inches	
0.0 degrees 1st end lydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: Ibrasion resistant and oil resistant leasuring Method And Length: 00.000 inches	
Iydrostatic Test Pressure: 00.0 pounds per square inch Duter Covering Environmental Protection: ubrasion resistant and oil resistant Ieasuring Method And Length: 00.000 inches	
00.0 pounds per square inch Duter Covering Environmental Protection: Ibrasion resistant and oil resistant Ieasuring Method And Length: 00.000 inches	
Duter Covering Environmental Protection: Ibrasion resistant and oil resistant Ieasuring Method And Length: 00.000 inches	
brasion resistant and oil resistant Ieasuring Method And Length: 00.000 inches	
leasuring Method And Length: 00.000 inches	
00.000 inches	
hread Series Designator:	
lpsm 1st end	
helf Life:	
l/a	
Init Of Measure:	
Demilitarization:	
lo	
iig:	