

View Online at <https://aerobasegroup.com/nsn/4720-00-359-0464>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

End Application:

Aircraft, f-16

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Thready Qty Per Inch (tpi):

24 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

30.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.219 inches

Special Features:

Weapon system essential

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Uns and unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0