## NSN 4720-00-363-4390

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-363-4390

Cross Sectional Shape:
Round
Thread Class:
2b and 2a 1st end
Thread Direction:
Right-hand and right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-565.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Hose Or Tubing Specification/std Data:
Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal and external tube 1st end
Second End Relationship With First End:
Not identical
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.375 inches and 0.625 inches 1st end
Outer Covering Environmental Protection:
Cold resistant and ozone resistant and water resistant and salt water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.750 inches working
Special Features:
Inner conveying tube material-rubber: w/mtg bracket in center of hole and 2nd end is a banio type fitting with 7/16 in. Dia. Hole, unthreaded.

Media For Which Designed: Hydraulic fluid single response

9/16 in. Thick 13/16in. Square

## NSN 4720-00-363-4390

Nonmetallic Hose Assembly - Page 2 of 2



Unf and unf 1st end

**Specification Data:** 

Sae j1401-81343 national std/spec

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0