

View Online at <https://aerobasegroup.com/nsn/4720-00-368-9644>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.602 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.140 inches

**Minimum Inside Bending Radius:**

7.750 inches

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

16 2nd end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer spirally laid steel wire and 1st layer spirally laid steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

1.000 inches 2nd end

**Seat Angle:**

8.5 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.875 inches working

**Special Features:**

2 safety wire holes 180 degrees apart

**Media For Which Designed:**

Air and hydraulic fluid single response

**Thread Series Designator:**

Unjs 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0