Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-369-9689

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.190 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.520 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and 1st layer braided textile yarn and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth



Measuring Method And Length: 58.250 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A542a0